

# GL 800

Our reliable platform lift with screw-driven system for passenger and goods traffic.

- GL 800 lift for passenger and heavy goods traffic indoor and outdoor. Suitable settings: industries, workshops, restaurants, shops, bars, hospitals, hotels etc.
- Capacity of 800 kg.
- Shaft panels in film laminated steel sheet as standard performance. Tidy and durable.
- Easy to install.
- Advanced preassembly.
- Reasonable installation cost.
- Motorized emergency lowering system is standard equipment.
- Driving to the next lower level during a power failure.
- Call with impulse drive.
- Door activated light relay.



# GL 800

Technical data: Indoor and outdoor lift for wheelchair users and goods traffic.


STANDARD EQUIPMENT	GL 800
Drive system	Screw-driven with frequency control
Lifting capacity	800 kg
Lifting height	0-13 m with up to 6 landings
Lifting speed	0,15 m/s
Electrical connection	3-phase 400/240V 20A
Platform	1100x1700 mm
Shaft	1500x1800 mm
Pit or ramp	70 mm
Doors	A1 with electric lock, 900x2000 mm alt. A1 double door with electric lock, 1400x2000 mm
Colour	Filmlaminated steel sheet Dobel 1072 white



OPTIONS	GL 800
Frequency control	Std
Shaft panels in safety glass	3 sides
Glass doors	Yes
- A2:1 WxH	650x950 mm
- A2 WxH	650x950 mm + 650x550 mm
- A3 WxH	650x1590 mm
Fire-proof doors	Yes
Doors with different width and height	Yes
Other platform width	Yes, max 2,0 m <sup>2</sup>
Automatic door opener	Yes
Alarm telephone Safeline MX2	Std
Stainless	Yes
Different colour	Other Dobel colour
Key control	Yes
School control	Yes
UPS backup	Std
Remote controlled infralink	Yes
Outdoor variant	Yes



Retailer:



NAMI Lift AB

Box 36, SE-298 21 Tollarp, Sweden. T. +46 (0)44 31 33 44. F. +46 (0)44 31 01 35. www.nami.se